## seca mBCA 515 medical Body Composition Analyzer III



- Fast and easy assessment of body composition, e.g., fat mass and body water.
- Six modules for varied analysis of measurement data.
- Medically precise, validated against gold standard measurement results.
- Network-compatible with
  TCP/IP (LAN).
- Simple and convenient entry and read-out of results on swiveling touch-screen display.
- Electrodes on handrail give patients a firm stance and ensure reproducible results.
- Integrated scale with a weighing capacity of up to 300 kg.



## sheet seca mBCA 515

## seca mBCA 515:

A body composition analyzer that delivers medically precise results.

The medical Body Composition Analyzer (mBCA) from seca breaks down weight into several compartments that are important for medical purposes. The seca mBCA 515 is a medical body composition analyzer validated against the gold standard recognised by medical science.

Capacity3Graduation5Weight3Display8Power supplyFVoltage1Power frequency5Calibration class0	976 x 1,251 x 828 mm 300 kg 50 g < 150 kg > 100 g 36 kg 8.4" Touch-screen display, can be rotated 360° Power adapter 100 V-240 V 50 Hz-60 Hz (D)
Capacity3Graduation5Weight3Display8Power supplyPVoltage1Power frequency5Calibration class0	300 kg 50 g < 150 kg > 100 g 36 kg 8.4" Touch-screen display, can be rotated 360° Power adapter 100 V-240 V 50 Hz-60 Hz
Graduation5Weight3Display8Power supplyFVoltage1Power frequency5Calibration class6	50 g < 150 kg > 100 g 36 kg 8.4" Touch-screen display, can be rotated 360° Power adapter 100 V-240 V 50 Hz-60 Hz
Weight3Display8Power supplyFVoltage1Power frequency5Calibration class6	36 kg 8.4" Touch-screen display, can be rotated 360° Power adapter 100 V-240 V 50 Hz-60 Hz
Display  8    Power supply  F    Voltage  1    Power frequency  5    Calibration class  6	8.4" Touch-screen display, can be rotated 360° Power adapter 100 V-240 V 50 Hz-60 Hz
Power supplyFVoltage1Power frequency5Calibration class0	Power adapter 100 V-240 V 50 Hz-60 Hz
Voltage  1    Power frequency  5    Calibration class  0	100 V–240 V 50 Hz–60 Hz
Power frequency  5    Calibration class  0	50 Hz – 60 Hz
Calibration class	
	(III)
Interfaces	
	Ethernet
Compatible printers L	Laser printer and inkjet printer via PC software seca analytics 115
Bioelectrical Impedance Analysis	
Measurement method 8	8-point Bioelectrical Impedance Analysis
Type of electrode S	Stainless steel, three (3) pairs of hand electrodes, two (2) pairs of foot electrodes
Measurement frequencies 1	1; 1.5; 2; 3; 5; 7.5; 10; 15; 20; 30; 50; 75; 100; 150; 200; 300; 500; 750; 1,000 kHz
Measurements Ir	Impedance (Z), Resistance (R), Reactance (Xc), Phase angle ( $\phi$ )
Phase angle measurement range 0	0° to 20°
Measurement range Impedance 1	10 Ω to 1,000 Ω
Measurement segments F	Right arm, left arm, right leg, left leg, right half of body, left half of body, torso
Measurement current 1	100 μΑ
	All modes at frequencies of 5 kHz and 50 kHz (max. 17 seconds) All modules at all frequencies (max. 90 seconds)
Technical data for scale	
Capacity V V	Weighing range 1 = 150 kg Weighing range 2 = 300 kg
Fine graduation V	Weighing range 1 = 50 g Weighing range 2 = 100 g
Accessories	
F	PC software seca analytics 115 (with one workstation license included)

Г

L

