

# PROFESSIONAL ASPIRATORS - HIGH VACUUM



CE 0051  
EN ISO 10079-1  
Class I  
Type B



MADE IN ITALY

28280-1

28244-6

1 l Autoclavable Jar

## ASPEED PROFESSIONAL SURGICAL ASPIRATORS

Piston-type continuous cycle electric aspirators give high performance and great durability. Equipped with a protective thermal cut-out relay. They require no maintenance or lubrication. A motor-protector cap totally prevents aspirated

liquids or secretions from reaching and damaging the vacuum pump. Ideal for clinical use.

GIMA code	ASPEED ASPIRATORS	Power	Pump	Case
28244	Aspeed 15 l	230 V	single	metal
28245	Aspeed 22 l	230 V	double	metal
28280	Aspeed 2 15 l	230 V	single	plastic
28281	Aspeed 2 22 l	230 V	double	plastic

GIMA code	ACCESSORIES AND SPARES FOR ASPEED
28255	Hydrophobic bacterial filter
28258	Autoclavable jar 1l with cover
28259	Disposable suction liner
25480	Silicone tube 6x12 mm - roll of 30 m
28254	Adaptor to connect catheter to silicone tube
28261	Adaptor kit to use jar 1l (28258) with ASPEED manufactured before 2007

**STANDARD ACCESSORIES**  
Autoclavable polycarbonate jar 1,000 cc with safety valve (overflow protection)  
Disposable suction liner 1 l  
Antibacterial hydrophobic filter  
Sterile disposable cannula  
Sterile manual flow regulator  
Set of atoxic sterilizable silicone tubes  
Power Cable  
User Manual: GB, FR, IT, DE, ES

	ASPEED		ASPEED 2	
	28244	28245	28280	28281
Operating voltage:	230 V-50 Hz		230 V - 50/60 Hz	
Bottle capacity:	1 l		1 l	
High vacuum:	high flow	high flow	low flow	high flow
Air flow:	15 l/min	22 l/min	15 l/min	22 l/min
Adjustable vacuum level:	0 ÷ -0.85 bar (0 ÷ -85 kPa)			
Weight:	3.5 kg	4.2 kg	2.7 kg	3.4 kg
Case material:	metal		plastic	
Noise level:	53 dBA	63 dBA	63 dBA	63 dBA



# ASPEED 3.0 PROFESSIONAL SINGLE PUMP ASPIRATOR

- 28279 ASPEED 3.0 ASPIRATOR 16 l/min - 1 l
  - 28319 ASPEED 3.0 ASPIRATOR 16 l/min - 2 l
- Portable, compact reliable aspirator ideal for small surgery. Piston type continuous cycle electric medical device. High vacuum low flow. No maintenance or lubrication.

MADE IN ITALY

TECHNICAL SPECIFICATIONS	
Operating voltage:	230 V - 50 Hz
Power consumption:	max 150 VA
Bottle capacity:	1 l (28279) or 2 l (28319)
High vacuum:	low flow
Air flow:	16 l/min
Adjustable vacuum level:	0 ÷ -0.65 bar (0 ÷ -65 kPa)
Size:	300x170xh 260 mm
Weight:	2.3 kg
Noise level:	65 dBA
Operating cycle:	continuous
Class:	II
Type:	BF

**STANDARD ACCESSORIES**  
Autoclavable polycarbonate jar 1,000 cc or 2,000 cc with safety valve (28258 or 28294)  
Disposable liner 1 l (28259) only for 28258  
Antibacterial hydrophobic filter  
Sterile disposable cannula  
Sterile manual flow regulator  
Set of atoxic sterilizable silicone tubes  
Power Cable  
User Manual: GB, FR, IT, DE, ES



28279



28319

Autoclavable jar 1l or 2l can be used with both models

CE 0051



Disposable liner (28259) has to be used within jar 1l (28258) by removing the blue lid



28259

GIMA code	ACCESSORIES AND SPARES FOR ASPEED
28255	Hydrophobic bacterial filter - spare
28258	Autoclavable jar 1 l with cover
28294	Autoclavable jar 2 l with cover
28259	Disposable suction liner 1 l - spare
25480	Silicone tube 6x12 mm - roll of 30 m
28254	Adaptor to connect catheter to silicone tube